



ECO-LINE



Blue 1 BVBA
Waaslandlaan 24
9160 Lokeren
Belgium

Btw-nr.: BE 0879.058.639
SWIFT-CODE: KREDBEBB
IBAN: BE53 7330 3267 1953
KBC bank 733-0326719-53

Tel. +32 9 349 37 51
Fax. +32 9 349 37 52
mail: info@blue1.be
RPR Antwerpen

Onze algemene aan- en verkoopvoorwaarden op de keerzijde of op www.blue1.be zijn van toepassing.
Nos conditions générales de vente au verso ou sur www.blue1.be sont d'application.

BLUE1 Eco-Line

Speciaal ontwikkeld voor u als vloothouder om op een:

Eenvoudige
Snelle
Gecontroleerde
Gebruiksvriendelijke
Veilige
...

manier AdBlue te kunnen tanken in uw nieuwe vrachtwagen voorzien van de laatste SCR technologie.

De Blue 1 Eco-line is een 3000L of 5000L-tankinstallatie die zeer gebruiks- en onderhoudsvriendelijk is en die u een constante continuïteit kan garanderen.

Standaard uitrusting:

- *3000L of 5000L tank geïntegreerd in geïsoleerde behuizing*
- *verwarming*
- *RVS vulleiding*
- *DDS-coupling*
- *Continu niveaumeting*
- *Overloopbeveiliging*
- *8,5 m slang*
- *Elaflex-pistool ZVA AdBlue*
- *Volledige RVS vloeistofleiding*

Voor meer informatie kan u ons steeds contacteren via:

Blue1
Waaslandlaan 24
9160 Lokeren
Tel: +32 9 349 37 51
Fax: +32 9 349 37 52
www.blue1.be
info@blue1.be

TECHNICAL SPECIFICATIONS BLUE1 ECO-LINE

- Concept:**
- ☑ Housing from insulated Sandwich elements.
 - ☑ 2 compartments:
 - √ Compartment 1 is tight and acts as a bund
 - √ Compartment 2 is the technical room
 - ☑ Integrated Anti freeze heating
 - ☑ Outside colour: white,
 - Optionals:**
 - √ Hot version: ventilation system activated by thermostat
 - √ Removable side element technical room
 - Versions:** **BL-5.000**
 - Volume : 5.000L
 - Dimensions: L = 3370mm, D = 1530 mm, H = 2317 mm
 - Weight (empty tank) : 750kg

- Tank:** *Installed into compartment 1*
- Type: Single wall
 - Material: Polyethylene
 - Pump: Submersible pump type LEADER Ecodiver 1000A

- Filling point:** Separated Stainless Steel filling tube integrated in the technical compartment
- ☑ 2" dry coupling
 - Overfill protection plug type Fafnir
 - Level indicator LCS
 - overfill prevention

- Refuelling:** *Installed into compartment 2*
- ☑ Standard foreseen with hose reel system with 8m operational length.
 - ☑ Elaflex automatic Ad Blue nozzle with integrated magnet.
 - ☑ Max flow 40l/min.
 - ☑ Complete Stainless steel Blue 1 panel with isolated door.
 - ☑ Not approved for public use

Flow measurement:

1. Display type ALX 701:

- Performances:
- ☑ Command for 1 pump & display of delivered fuel.
 - ☑ Storage of litre totals.
 - ☑ Calibration factor of the measuring room.
 - ☑ Output 10 pulses pro litre
- Specifications:
- ☑ Metal coated housing
 - ☑ Electronic card with 6 digit lighted display
 - ☑ Automatic display reset
 - ☑ 2 fuses 2A
 - ☑ Plug connectors for divers connections
 - ☑ 4 bolts M4 for fixation
 - ☑ Dimensions: L=180mm; H=120mm; D=60mm

2. Measuring room PIUSI

Measuring principle		Turbine / impeller
Materials		Body: AISI 316I Magnets: Samarium-cobalt Seals: Viton Impleer: Polypropylene
Connection	Inch	1" male threated
Resolution	L/impulse	0.011
Flow rate	L/minute	Max 40l/min
Storage temperature	°C	-20 / +70
Storage humidity	R.U.	95%
Operating temperature	°C	-10 / +60 °C
Head loss (at 40L/min)	Bar	0.05
Precision	%	+/-1
Repeatability	%	+/-0.4
Type of impulse		Clean contact (reed switch)
Max current	mA	100
Max voltage	Volt ac/dc	28
Impulse/liter	Number	92
Max. operating pressure	Bar	20
Max. bursting pressure	Bar	40

Electrical connections:

- ☑ For non hazardous area
- ☑ 1 x 230VAC, 16A (3 x 2.5mm²)
- ☑ EU Directive Low Voltage 73/23/EEG, updated 93/68/EEG