



Blue1 Naked

The Blue1 Naked is specially engineered for above ground AdBlue storage. With the Blue1 Naked we can offer a complete range of volumes from 1000L up to 15000L which can be equipped with 1 up to 5 separate pumps to give you a maximum benefit.

This solution, which offers an optimal combination between price and quality, is engineered and built according to the highest quality standards, to make sure that your AdBlue keeps its 100% purity.



Product Specifications

- Plug and play
- Bunded
- Volume 1000L to 15000L
- Stainless Steel Piping
- DDC-coupling
- Submersible Pump 40L/min
- Dry run security
- Heating
- Level gauge + indication
- Overfill protection
- Telemetry (option)
- DIBT (option)
- KIWA (option)
- EX-conformity (option)

Principle:

The housing is built up out of insulated fibreglass reinforced sandwich elements and is divided into 2 compartments:

- Compartment 1 is completely liquid tight and acts as a bund
- Compartment 2 is the technical compartment in which the unit can be serviced and filled up.

The temperature inside the unit is constantly controlled to ensure the operational temperature of the AdBlue.

Filling up the unit:

The unit can be filled up through the door at the side of the unit which gives access to the technical compartment of the installation or through a side fill panel which is an option. The Dry Disconnect Coupling makes sure that all deliveries will occur without leakage and on the other hand the overfill prevention will make sure that an overfill off the unit is impossible.

Connection to Industrial satellite or commercial dispenser:

The unit is completely prepared to connect all types of industrial and commercial dispensers or satellites. The Blue1 Naked is standard equipped to deliver AdBlue for 1 dispenser, but can be upgraded to deliver AdBlue for up to 5 dispensers. The installation can also be fitted with a connection kit for dispenser to mount a dispenser directly at the side of the installation, in this case the side fill is a mandatory option.

Level indication:

The volume inside the unit is constantly monitored and is shown off on a display.

Piping:

All piping is approved up to 16 bar and is always in Stainless Steel.



Waaslandlaan 24
9160 Lokeren
Belgium

Tel: +32 9 349 37 51
Fax: +32 9 349 37 52
Mail: info@blue1.be
Website: www.blue1.be



Side fill (optional)





Measuring and monitoring in real time is an essential tool in a world of short global communication lines. Therefor Blue1 developed a complete telemetry system which covers hardware, communication and visualization.

ONE PARTNER FOR

- hardware
- communication
- web based backoffice
- installation, maintenance and service



NO SOFTWARE INSTALLATION

ONE SIMCARD WITH WORLD COVERAGE


PROVEN TECHNOLOGIE

REAL TIME DATA CONVERTED TO VALUE ADDED INFORMATION

STATE OF THE ART HIGH END BACKOFFICE AND USER INTERFACE

Product Specifications

- Plug and play
- Bunded
- Volume 1000L to 15000L
- Stainless Steel Piping
- DDC-coupling
- Submersible Pump 40L/min
- Dry run security
- Heating
- Level gauge + indication
- Overfill protection
- Telemetry (option)
- DIBT (option)
- KIWA (option)
- EX-conformity (option)



Waaslandlaan 24
9160 Lokeren
Belgium

Tel: +32 9 349 37 51
Fax: +32 9 349 37 52
Mail: info@blue1.be
Website: www.blue1.be





Product data specifications Blue1 Naked

Product Specifications

- Plug and play
- Bunded
- Volume 3000L to 15000L
- Stainless Steel Piping
- DDC-coupling
- Submersible Pump 40L/min
- Dry run security
- Heating
- Level gauge + indication
- Overfill protection
- Telemetry (option)
- DIBT (option)
- KIWA (option)
- EX-conformity (option)

	Volume	Length	Width	Height	Kg
Dimensions	1000L	2.010 mm	860 mm	1.995 mm	400 kg
	1500L	2 010 mm	860 mm	1.995 mm	450 kg
	2000L	2 520 mm	860 mm	1.995 mm	550 kg
	3000L-S	2.820 mm	990 mm	2.320 mm	700 kg
	3000L	2.860 mm	1.170 mm	2.320 mm	700 kg
	4000L	2.860 mm	1.170 mm	2.320 mm	750 kg
	5000L	3.370 mm	1.530 mm	2.317 mm	750 kg
	7.500L	4.600 mm	1.530 mm	2.317 mm	980 kg
	10.000L	5.800 mm	1.530 mm	2.317 mm	1.250 kg
	15.000L	9.260 mm	1.530 mm	2.450 mm	1.875 kg
Housing	Insulated sandwich panels integrated in fibreglass structure and acts as a bund, colour: standard white				
Tank	Single walled / polyethylene / installed in compartment				
Flow rate	Between 30 and 40L/min or for cars/vans between 5 and 10L/min				
Pump	Submersible pump 1000W (and 1200W optional)				
Heating	Anti freeze heating 1500W / 3000W				
Piping	Stainless Steel 16 bar approved				
Filling point	In technical compartment / Dry Disconnect Coupling Side fill (optional)				
Level Sensor	4-20 mA				
Level indicator	standard				
Central controller	standard				
Overfill protection	Fafnir plug / active overfill alarm with reset button (optional)				
Leak detection	Sensor in bunded area to detect leakage off primary tank or overfill (optional) - Ex approved leak detection (option)				
Power supply	1x230 VAC, 16 A, 3x2,5mm ² , for non hazardous area				
Side fill	Optional (mandatory in case of connection kit for dispenser)				
EX coformity	Optional (EX II 3/- G, IIA T3)				
Connection kit for dispenser	Optional				
Telemetry	Optional				
Pressure reducing valve	Optional 1-6 bar with gauge (optional)				